



CLEANING ■ SEALING ■ MAINTENANCE

Sealing and maintenance solutions for all types of stone, porcelain, quarry, terracotta and glazed ceramic

TECH DATA SHEET 2010

LTP Antique Beeswax

A Medium Brown Wall and Floor Tile Polish

for use on travertine, slate, limestone, sandstone, tumbled marble, flamed and rough cut granite, terracotta, quarry and brick. provides an aged appearance.

LTP ANTIQUE WAX

A soft paste wax, blended from three types of wax which gives treated surfaces an excellent shine. It provides a resilient protective layer against water, dust, dirt and a variety of commonly found household contaminants. LTP Antique Wax comes ready to use and is easily applied by cloth before polishing to a finish. Suitable for use on travertine, limestone, sandstone, slate, tumbled marble, flamed and rough cut granite, terracotta, quarry and brick.

Directions for use:

The surface to be treated should be completely, clean, dry and any pre-polish sealer thoroughly cured. Stir well. Apply sparingly with a soft fluff-free cloth ensuring that the area of application is manageable. Quickly buff wax to a shine using a short haired brush, soft cloth or mechanical polisher.

Please Note: When using LTP Antique Wax on higher absorbency floors, the wax may be absorbed into the surface unevenly, consequently proving difficult to shine. Therefore, when treating such floors, it may be necessary to reduce the absorbency by applying a suitable impregnating sealer. LTP Antique Wax can be applied to surfaces that have been impregnated with LTP Boiled Linseed Oil, Stone Oil, Stone Oil Antique, Mattstone and Colour Intensifier. The type of impregnator used will depend on the type of material that is being sealed.

Coverage: On most floors, 1 litre /10 square metres (two coats).

Maintenance: Routinely sweep the floor and wash with LTP Waxwash. Ensure that areas where the seal has been worn or damaged are re-waxed. Apply a fresh coat of LTP Antique Wax to your floor should it begin to show signs of stain absorption. This should be done after the surface has been washed and allowed to thoroughly dry.

NB. Test the wax on an inconspicuous area prior to general application. LTP Antique Beeswax may not properly harden if too much polish is applied or if applied to surfaces containing moisture. In either case it may be difficult to obtain a shine. It will not polish properly if used on partially cured sealers or if the floor has not been properly pre-sealed. This product may be less ably applied in cold weather, in which case it may help to warm the can in tepid water (N.B. Do not use naked flame).

HEALTH & SAFETY

FLAMMABLE Contains Toluene and Xylene.

Harmful by inhalation and in contact with skin. Irritating to skin.

Wear suitable protective clothing and gloves. Allow good ventilation during application.

Keep out of the reach of children.

Keep away from sources of ignition; no smoking.

In case of swallowing seek medical advice.

UN 1263



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous

for beautiful surfaces we have the solutions...

LTP, Tone Estate, Milverton Road, Wellington, Somerset, TA21 0AN

T +44 (0) 1823 666213 F +44 (0) 1823 665685 E info@ltp-online.co.uk

www.ltp-online.co.uk

