

JAN 2008



TECHNICAL DATA SHEET

FRONT:

**LTP CLEAR BEESWAX
NATURAL CLEAR FLOOR AND WALL POLISH**

FOR TRAVERTINE, LIMESTONE, SANDSTONE, SLATE, MARBLE, GRANITE, TERRACOTTA, QUARRY
TILES AND BRICK.

BACK:

LTP Clear Beeswax

A soft paste wax, blended from three types of wax and gives treated surfaces an excellent shine and provides a resilient protective layer against water, dust, dirt and a variety of commonly found household contaminants. It comes ready to us. It is easily applied by cloth and then polished. Suitable for use on Travertine, limestone, sandstone, slate, marble, granite, terracotta, quarry tiles and brick.

Directions for use:

The surface to be treated should be completely, clean and dry and any pre-polish sealer thoroughly cured or oxidised. Apply sparingly with a soft fluff-free cloth, working in manageable areas at a time. Quickly buff wax to a shine using a short haired brush or mechanical polisher.

Please Note - when using Clear Beeswax on higher absorbency floors, the wax may be absorbed into and below the surface, consequently proving difficult to shine. Therefore, when treating such floors, it may necessary to reduce the absorbency by applying a primary seal of LTP Boiled Linseed Oil, LTP Cleartone, LTP Mattstone or LTP Colour Intensifier prior to application of Beeswax.

Coverage:

On most floors - 1 litre LTP Clear Beeswax/10 square metres of floor (for two coats).

*NB. Fully hardened Clear Beeswax may dry slightly opaque (slightly white), especially if it is over applied. This whiteness may show up more on darker, rougher tiles. Therefore, it is advisable to test the wax on an inconspicuous area prior to general application. LTP Clear Beeswax may not properly harden if too much polish is applied or if it applied to surfaces containing moisture. In either case it may be difficult to obtain a shine. It will not polish properly if used on partially cured sealers or if the floor has **not** been properly pre-sealed. This product may be less ably applied in cold weather, in which case it may help to warm the can in tepid water (N.B. Do not use naked flame).*

Attention

FLAMMABLE

Contains Toluene, Keep out of the reach of children, Use gloves to apply, Avoid contact with eyes and skin, allow good ventilation during application., keep away from sources of ignition, no Smoking, harmful by inhalation, in contact with skin and if swallowed., In case of swallowing seek medical advice.



Maintenance:

Routinely sweep the floor and wash with LTP Waxwash. Ensure that areas where the seal has been worn or damaged are re-waxed. Apply a fresh coat of LTP Clear Beeswax to your floor should it begin to show signs of stain absorption. This should be done after the surface has been washed and allowed to dry thoroughly.

**LTP, Tone Estate, Milverton Road, Wellington, Somerset, TA21 0AN
Tel: +44(0)1823-666-213 www.ltp-online.co.uk Fax: +44(0)1823-665-685**

This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area