



# CLEANING ■ SEALING ■ MAINTENANCE

Sealing and maintenance solutions for all types of stone, porcelain, quarry, terracotta and glazed ceramic

## CRACKLE GLAZE PROTECTOR TECHNICAL DATA SHEET REF: 29/.5

### LTP CRACKLE GLAZE PROTECTOR

Forms a clear colourless barrier. Helps protect porous tiles from penetration by water, dirt, oil, grease, limescale and other commonly found household contaminants. For use on crackle glaze tiles and grout joints.

### Directions for use:

Ensure that the tile surface is clean and dry. Any tiles that are to be wet cut should be protected with at least one coat of sealer. Once the tiles have been fixed and before grouting apply one coat of sealer to the surface with a sponge or soft cloth and then buff immediately into the surface with a separate soft cloth. This should be done until all excess is removed. Leave for a minimum of two hours before grouting with normal grouts. If coloured or pigmented grouts are used, leave for a minimum of 24 hours. Once the grouting is dry (min 24hrs) apply a second coat of sealer to the surface also covering the joints. After 48 hours the surface can be cleaned as normal. Use a dry cloth to remove any excess from non absorbent surfaces.

### Health & Safety:

#### FLAMABLE

Contains: naphtha (petroleum) hydroesulpherised heavy (<0.1% benzene). Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.

Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking. Keep away from food, drink and animal feeding stuffs. Keep out of reach of Children. Do not empty into drains, dispose of this material and its container at a hazardous or special waste collection point. Wear suitable gloves. If swallowed, seek medical advice immediately and show this container or label. Use only in well ventilated areas. Avoid release to the environment. Refer to special instructions/safety data sheets.



VOC STATEMENT  
EU Limit value for this product  
(Cat A/h) 750g/L (2010)  
This product contains max  
710g/L VOC

UN 1300

### Coverage:

Approximately 5 sq.m per 500ml (2 coats)

### Storage information:

Store in a cool, dry, frost free environment

### Notes:

#### Important:

Protect sensitive surfaces against splashes. Always test the product in an inconspicuous area prior to general application. Do not use in direct sunlight. All spillages should be wiped up immediately.

Crackle Glaze Protector is not suitable for use on tiles that have been grouted with an epoxy grout.

#### Drying Time:

Approximately 30-40 minutes. Becomes fully effective after approx 48 hours.

### Maintenance

Wash tiles with a mild, non acidic detergent. LTP Stonewash Spray.



*This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area*

*for beautiful surfaces we have the solutions...*

LTP, Tone Estate, Milverton Road, Wellington, Somerset, TA21 0AN

T +44 (0) 1823 666213 F +44 (0) 1823 665685 E info@ltp-online.co.uk

www.ltp-online.co.uk

July 2011

