



**TECHNICAL DATA SHEET**

FRONT:

**LTP GLAZE PROTECTOR**

**LOW MAINTENANCE SELF SHINE SEALER**

**FOR GLAZED CERAMIC, UNPOLISHED PORCELAIN & VITRIFIED QUARRY TILES**

BACK:

**LTP Glaze Protector**

**Suitable for Interior use only**

Low maintenance self shine sealer for glazed ceramic, unpolished porcelain and vitrified quarry tiles. Protects and embellishes all types of tiles. Highly resistant to wear and stains. Slip resistant. Facilitates maintenance and cleaning.

**Directions for use:** Ensure surface to be treated is completely clean, dry and free from cement and grout stain (see LTP Grout Stain Remover).

**Preparation of the floor:** First clean and degrease the floor with LTP Grimex taking care to rinse well. Leave to dry out thoroughly.

**Application:** Shake the bottle well before use and pour the product undiluted onto the floor. Apply a thin coat evenly with a damp cloth or sponge with out rubbing. Leave to dry for 30 minutes. Rinse the floor cloth or sponge with water after use. For a higher protection or a glossier finish, apply a second coat similarly one hour later. NB. Do not over apply as too many coats may cause unsightly build up of LTP Glaze Protector and/or reduce the efficiency of the product. If in doubt, experiment on spare tiles to establish the optimum number of coats before general use. **NB. Do not wash your floor for 3 days after the final coat of LTP Glaze Protector.** This allows the sealer to fully polymerise (harden) on to the surface.

**Coverage:** Approximately 30-40m<sup>2</sup> per litre (one coat) depending on substrate porosity.

**Attention:** Keep out of reach of children. Store in a frost proof place.  
Avoid using strong detergents to wash surfaces treated with LTP Glaze Protector.  
Do not use below freezing. After contact with skin, wash with soap and water.  
For interior use only. Not suitable for use in wet areas e.g. showers or wet rooms.  
Do not apply on to rubber floors.

**Maintenance:**

Routinely sweep the floor. Use LTP Floorshine to clean and protect the floor. In areas where the seal becomes worn, reseal using more LTP Glaze Protector. At some stage, complete renovation of the seal may be desired. In this case use LTP Grimex to strip the original seal before re-sealing with LTP Glaze Protector.

This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area

**LTP, Tone Estate, Milverton Road, Wellington, Somerset, TA21 0AN**

**Tel: 01823-666-213**

**Fax: 01823-665-685**

**[www.ltp-online.co.uk](http://www.ltp-online.co.uk)**

**[info@ltp-online.co.uk](mailto:info@ltp-online.co.uk)**