



CLEANING ■ SEALING ■ MAINTENANCE

Sealing and maintenance solutions for all types of stone, porcelain, quarry, terracotta and glazed ceramic

TECH DATA SHEET 2010

FRONT:

LTP Glaze Protector

Low maintenance self shine sealer

FOR INTERIOR USE ONLY

Retains the 'just washed' look on glazed ceramic & porcelain, unpolished porcelain & vitrified quarry tiles.

BACK:

LTP Glaze Protector

Suitable for interior use only (Not wet rooms or shower enclosures)

Low maintenance self shine film forming sealer for glazed ceramic and porcelain, unpolished porcelain and vitrified quarry tiles. Protects and embellishes the surface. Highly resistant to wear and stains. Facilitates maintenance and cleaning. Leaves surfaces with a 'just washed' look.

Directions for use:

Newly installed surfaces - ensure surface to be treated is completely clean, dry and free from cement and grout stain (see **LTP Grout Stain Remover**).

Existing surfaces - first clean and degrease surfaces with **LTP Grimex** taking care to rinse well. Leave to dry out thoroughly (24 hrs). Any retained moisture in the grout joints may cause the **LTP Glaze Protector** to dry opaque or prevent the seal from reaching full hardness.

Application:

Apply using a J cloth saturated with the solution. Pour contents into a separate container. Dip cloth into the solution and wring out. Fold the cloth and apply evenly to the surface without rubbing. Apply until an evenly thin film is created (Avg. 3 times). Allow to dry (1 hr). For a glossier finish further coats should be applied at right angles to the first (max.6).

Do not over apply as too many coats may cause unsightly build up and/or reduce the efficiency of the product. Hardens after about an hour but will take a further three days to achieve full hardness and become fully water resistant. If in doubt, experiment on spare tiles to establish the correct method of application and optimum number of coats before general use. Rinse the floor cloth with water after use.

Maintenance:

Routinely sweep the floor. Use **LTP Floorshine** to clean and protect treated surfaces. In areas where the seal becomes worn, apply more **LTP Glaze Protector**. At some stage, complete renovation of the seal may be desired. In this case use **LTP Grimex** to strip the original seal before re-sealing.

Coverage:

Approximately 30-40m² per litre (one coat) depending on substrate porosity.

Attention:

Keep out of reach of children. Store in a frost proof place. Avoid extremes of temperature. Avoid using strong detergents to wash surfaces treated with LTP Glaze Protector. Do not use below freezing. After contact with skin, wash with soap and water. Do not apply on to rubber floors.

This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area

for beautiful surfaces we have the solutions...

LTP, Tone Estate, Milverton Road, Wellington, Somerset, TA21 0AN

T +44 (0) 1823 666213 F +44 (0) 1823 665685 E info@ltp-online.co.uk

www.ltp-online.co.uk

