



# CLEANING ■ SEALING ■ MAINTENANCE

Sealing and maintenance solutions for all types of stone, porcelain, quarry, terracotta and glazed ceramic

## GRIMEX TECHNICAL DATA SHEET REF: 7/5/1

### LTP GRIMEX

#### LTP Grimex Heavy Duty Grime Remover For interior & exterior use

Suitable for travertine, limestone, sandstone, slate, marble, porcelain, granite, terracotta, quarry tiles, brick & external paving.

Effective for removing oil, grease, ingrained dirt grime and old wax layers.

**Important:** - Test the solution on an inconspicuous area before general application. Any alkalinity remaining on surfaces treated with this product should be completely neutralised. This may be done with a little clean water applied by sponge.

### Directions for use:

#### In mild cases and on absorbent tiles:

Dilute one part LTP Grimex in 10 parts warm water. Apply with a cloth or mop. Wipe off thoroughly with a clean damp cloth.

#### In more severe cases:

Dilute one part LTP Grimex in 3 parts warm water. Apply liberally, spreading over surface of tiles. If necessary agitate with a scrubbing brush. Leave to react for 5-10 minutes, keeping wet with additional solution. Agitate surface again, mop up and rinse thoroughly with clean water.

#### In extremely severe cases:

Use undiluted and agitate with scrubbing brush or mechanical scrubber if necessary. Neutralise treated surface with clean water after use.

### Health & Safety:

#### Irritating to eyes and skin. Harmful by inhalation.

Keep out of reach of children. Use gloves to apply. Avoid contact with eyes and skin. In case of contact with eyes rinse immediately with plenty of water and seek medical advice. If swallowed seek medical advice and show this container or label. Dispose of this material and its container to hazardous or special waste collection point. Refer to special instructions/material Safety Data Sheets.



### Coverage:

In mild cases	- approximately 50m <sup>2</sup>
In more severe cases	- approximately 20m <sup>2</sup>
In extremely severe cases	- approximately 5-10m <sup>2</sup>

### Storage information:

Store in a cool, dry, frost free environment

### Notes:

This product should not be used for every day cleaning of floors or walls that have been sealed.

Cleaned surfaces that have been previously sealed should be re-sealed after using this product. This should be done after rinsing with plenty of clean water and once surfaces have had sufficient time to thoroughly dry (min 24hrs).



*This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area*

*for beautiful surfaces we have the solutions...*

LTP, Tone Estate, Milverton Road, Wellington, Somerset, TA21 0AN  
T +44 (0) 1823 666213 F +44 (0) 1823 665685 E info@ltp-online.co.uk

www.ltp-online.co.uk

July 2011

