



TECHNICAL DATA SHEET

FRONT:

Grout & Tile Protector (Aerosol)

- Easy to apply, quick drying spray-on formula
- Long lasting protection against water, dirt, grease, mould and limescale
- Suitable for both wall and floor grout and natural stone borders
- Overspray dries invisible

LTP Grout & Tile Protector forms a colourless barrier and helps to protect porous wall and floor grout joints from penetration by water, dirt, oil, grease and limescale, making treated surfaces easier to keep clean. Ideal for use in wet rooms and shower enclosures. Used as a 'top up coat' this product is an easy way to further protect natural stone and all other types of masonry surface. Overspray on most surfaces will completely dissipate and not leave any hard to remove residue. When sealing a porous stone it is advisable to use a suitable liquid impregnator such as LTP Mattstone or LTP Colour Intensifier before finishing with LTP Grout & Tile Protector to achieve the best result.

Suitable for internal and external use.

Coverage per 600ml:

600 linear metres depending upon the size of grout joint and number of coats required.

5 - 25 sq.m of tile and grout depending upon the porosity and the number of coats required.

Directions for use:

Areas to be treated must be cleaned. Older contaminated and dirty grouting should be cleaned with LTP Grimex and then rinsed thoroughly. Newly grouted surfaces should be left to cure for 20-30 minutes and should be clean and free from dust before application. Always test the product on an inconspicuous area for suitability before general application. Shake can well. Spray 15-20 cm from the surface and spray in a sweeping motion. Touch dry within 5 minutes. A 2-3 hour curing time is recommended upon completion before allowing traffic. For wet areas including shower enclosures and wet rooms allow the sealer to cure for a minimum of 24 hours before use. Test area after application with a little water, if the water is absorbed, a second or even third coat may be required to obtain maximum performance. Use only in open or well ventilated areas. Open windows and if possible use fans to circulate air. It is recommended that a suitable respiratory mask be worn at all times. Overspray on highly polished porcelain or stone and highly glazed surfaces may in some cases leave a slight residue, in which case wipe up any excess within 5 minutes. Stubborn residues left on the surface can be removed with the application of more **LTP Grout & Tile Protector** which should then be buffed off immediately.

Do not spray on to acrylic or stained surfaces such as cabinets and stained timber skirting boards. Mask and protect these surfaces before application.

Shake can well before use.

Maintenance:

Do not use harsh abrasive cleaning agents. Clean treated areas with water and a mild PH neutral detergent like LTP Waxwash or LTP Stonewash. In some instances it may be necessary to use a stronger cleaner to remove stubborn surface marks, in which case you may need to re-seal treated areas.

HEALTH & SAFETY

Extremely flammable. Irritating to skin. Very toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment. Vapours may cause drowsiness and dizziness

Keep out of reach of children. Keep away from sources of ignition- No smoking. Do not breathe vapour/spray. Avoid contact with skin and eyes. Do not empty into drains. Use only in well-ventilated areas. Pressurized container; protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.

UN 1950

USE ONLY AS DIRECTED



LTP Tone Estate, Milverton Road, Wellington, Somerset, TA21 0AN

Tel: 01823-666-213 Fax: 01823-665-685 www.ltp-online.co.uk