



TECHNICAL DATA SHEET

FRONT:

LTP WALL & FLOOR GROUT PROTECTOR

FOR POROUS GROUT IN KITCHENS, BATHROOMS ETC. PROTECTS AGAINST WATER, DIRT, GREASE, MOULD AND LIMESCALE..

SUITABLE FOR INTERIOR & EXTERIOR USE

BACK:

LTP Wall & Floor Grout Protector

Suitable for Interior & Exterior use

Forms a clear, colourless barrier. Helps protect absorbent, porous grout joints.

Directions for use:

Important: LTP Wall and Floor Grout Protector is intended for use only on porous grout joints between non-porous glazed or highly vitrified ceramic tiles (not epoxy grout).

Ensure that the grout surface to be treated is completely clean and dry. Allow grout to dry for 24 hours after cleaning. Apply a generous coat of LTP Grout Protector using a small paintbrush and allow to soak in. To avoid leaving a film on the adjoining tiles, wipe away any surplus as you go with a clean, fluff-free cloth, dampened, if necessary, with a little white spirit. Do not treat more than an area of 2 or 3 square metres at a time to ensure that all of the product is absorbed into the grout. Remove any excess LTP Grout Protector which is not absorbed into grout joints within 20 minutes of application. Repeat process after one hour. If necessary, further treatments can be applied after an hour or so. After 48 hours the surface can be cleaned as normal. Use a dry cloth to wipe away any excess from non-absorbent surfaces.

Please Note:

Protect glass, sanitary ware, polished surfaces, plastics, painted and other sensitive surfaces against splashes. Do not allow excess to dry on the surface. Wipe away carefully. If in doubt, test the product on a small area. Do not use in direct sunlight or in temperatures over 25 degrees C.

Drying Time: Approx 30-40 minutes. Becomes fully effective after approx 48 hours.

Maintenance: If necessary, wipe over grout joints using a mild detergent. Use LTP Grimex to remove stubborn surface marks, in which case you may need to re-seal treated areas.

HEALTH & SAFETY

Contains: White Spirit (naphtha petroleum, hydrodesulphurised heavy (<0.1% benzene). FLAMMABLE.

Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.

Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.

Keep out of the reach of children. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Wear suitable gloves and goggles. If swallowed, seek medical advice immediately and show this container or label. Use only in well ventilated areas. Avoid release to the environment. Refer to special instructions/Safety Data Sheets.

UN 1993



Very High VOC content, > 50%.
VOC's (Volatile Organic Compounds)
Contribute to atmospheric pollution.

LTP, Tone Estate, Milverton Road, Wellington, Somerset, TA21 0AN

Tel: 01823-666-213

Fax: 01823-665-685

www.ltp-online.co.uk

info@ltp-online.co.uk