



CLEANING ■ SEALING ■ MAINTENANCE

Sealing and maintenance solutions for all types of stone, porcelain, quarry, terracotta and glazed ceramic

TECH DATA SHEET 2010

FRONT:

LTP Grout Stain Remover Cement, Limescale & Grout Residue Remover

for glazed and un-glazed ceramics, slate, quarry tiles, brick, terracotta & stone.
suitable for interior & exterior use

BACK:

LTP Grout Stain Remover *Suitable for Interior & Exterior use*

A rapid action cleaning agent for removing cement residues, grout stain, efflorescence and other similar deposits from glazed and unglazed ceramics, slate, quarry tiles, brick, terracotta, and stone. May be used in dilute or concentrated form.

Important: - This product may not be suitable for use on all floor materials. Test the solution on a small inconspicuous area prior to general application. When using acid solution, prolonged contact with grout joints should be avoided. Any acidity remaining on surfaces treated with this product should be completely neutralised after use. This may be done with a little clean water applied by sponge.

Directions for use:

In mild cases and on absorbent tiles:

Dilute 1 part Grout Stain Remover in 4 parts warm water. Apply with a cloth or sponge wrung out in the solution. Wipe off thoroughly with a clean damp cloth.

In more severe cases:

Dilute 1 part Grout Stain Remover in 1 part warm water. Apply liberally and spread over surface of tiles. If necessary, agitate with a scrubbing brush and leave to react for 5-10 minutes, keeping wet with additional Grout Stain Remover solution. Mop up and rinse thoroughly with clean water.

In extremely severe cases:

Use undiluted and agitate with scrubbing brush if necessary. Neutralise treated surface with clean water after use.

Coverage: Approximately 5-25m² per litre.

Attention:

Keep out of reach of children.

Avoid contact with eyes and skin.

In case of contact with eyes rinse with plenty of water and seek medical advice.

In case of swallowing seek medical advice immediately and show this label.

Contains Hydrochloric Acid <10%. Wear suitable gloves and eye protection.

Unless you fully understand the methods of application, DO NOT use LTP Grout Stain Remover on surfaces that are calcareous, sensitive to acids (e.g. stainless steel, chrome, enamel etc), or contain lime (i.e. marble or limestone). In conditions of extreme humidity LTP Grout Stain Remover vapour may react with acid sensitive surfaces. Any contaminated surface should be rinsed off immediately with plenty of clean water. Do not use when under floor heating systems are in operation.

This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area

for beautiful surfaces we have the solutions...

LTP, Tone Estate, Milverton Road, Wellington, Somerset, TA21 0AN

T +44 (0) 1823 666213 F +44 (0) 1823 665685 E info@ltp-online.co.uk

www.ltp-online.co.uk

