



TECHNICAL DATA SHEET

FRONT:

**LTP IRONWAX GLOSS
GLOSS FINISH SEALER**

FOR TRAVERTINE, LIMESTONE, SANDSTONE, SLATE, UN-POLISHED MARBLE, TERRACOTTA, QUARRY, BRICKS, TERRAZZO AND CONCRETE.

SUITABLE FOR FLOORS & WALLS

BACK:

**LTP Ironwax Gloss
Suitable for Interior use only**

Easy to apply, low maintenance self-shine gloss finish acrylic sealer. Enhances colour and texture. Protects against staining and stubborn dirt. Easy to maintain. May be used on travertine, limestone, sandstone, slate, un-polished marble, terracotta, quarry, bricks, terrazzo and concrete Suitable for domestic and commercial use.

Directions for use:

Ensure surface to be treated is completely clean, dry and free from cement and grout stain (see LTP Grout Stain Remover). Any moisture may cause the LTP Ironwax Gloss to dry opaque or prevent the seal from reaching full hardness. Using a sponge or soft fluff-free cloth, apply a thin coat of LTP Ironwax Gloss evenly in one direction. Do not rub or buff the surface but allow to dry (approx 1 hour). Apply a second coat at right angles to the first. Subsequent coats should be applied at right angles to the previous. Do not over apply as too many coats may cause unsightly build up and/or reduce the efficiency of the product. Hardens after about an hour but will take a further three days to achieve full hardness and become fully water resistant. If in doubt, experiment on spare tiles to establish the optimum number of coats before general use.

Coverage:

Approximately 15-30m² per litre (one coat) depending on substrate porosity.

Attention:

Avoid shaking the bottle prior to use. Frothing of liquid may lead to an inconsistent finish. Keep out of reach of children. Store in a frost proof place. Do not use below freezing. After contact with skin, wash with soap and water. Ironwax Gloss may not properly adhere to highly vitrified quarry tiles or ceramics. If in doubt, test on an inconspicuous area prior to general application. Avoid using strong detergents to wash floors treated with LTP Ironwax Gloss. On higher porosity floor materials such as terracotta and limestone LTP Ironwax Primer may be required prior to use of LTP Ironwax Gloss. **Do not empty into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings.**

Maintenance:

Routinely sweep the floor. Use LTP Floorshine to clean and protect the floor. In areas where the seal becomes worn, apply more LTP Ironwax Gloss. At some stage, complete renovation of the seal may be desired. In this case use LTP Grimex to strip the original seal before re-sealing.

This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area

LTP, Tone Estate, Milverton Road, Wellington, Somerset, TA21 0AN

Tel: 01823-666-213

Fax: 01823-665-685

www.ltp-online.co.uk

info@ltp-online.co.uk