



TECHNICAL DATA SHEET

FRONT:

LTP IRONWAX PRIMER

PRE-SEALER FOR IRONWAX GLOSS & IRONWAX SATIN

FOR USE ON POROUS TERRACOTTA OR STONE BEFORE FINISHING WITH IRONWAX GLOSS OR IRONWAX SATIN.

SUITABLE FOR FLOORS & WALLS

BACK:

LTP Ironwax Primer

Suitable for Interior use only

Easy to apply acrylic primer. Enhances the colour and texture of floors. Facilitates a good adherence of LTP Ironwax Gloss and Ironwax Satin. Suitable for use on porous terracotta and stone.

Directions for use:

Ensure surface to be treated is completely clean, dry and free from cement and grout stain. Any moisture may cause the LTP Ironwax Primer to dry opaque or prevent the seal from reaching full hardness. Using a damp sponge or soft fluff-free cloth, apply a thin coat of LTP Ironwax primer evenly in one direction. Do not rub or buff the surface but allow to absorb/dry (approx 1 hour). Subsequent coats (if required) should be applied at right angles to the previous. LTP Ironwax Primer will begin to harden after about an hour. Once dry, finish the surface with 1-2 coats of LTP Ironwax Gloss or LTP Ironwax Satin. If in doubt, experiment on spare tiles to establish the optimum number of coats before general use.

Coverage:

Approximately 10-20m² per litre (one coat) depending on substrate porosity.

Attention:

Avoid shaking the bottle prior to use. Frothing of liquid may lead to an inconsistent finish. Keep out of reach of children. Store in a frost proof place. Do not use below freezing. After contact with skin, wash with soap and water. On less absorbent surfaces such as slate, quarry tiles or travertine primer may not be required in this case just use LTP Ironwax Gloss or LTP Ironwax Satin. If in doubt, test on an inconspicuous area prior to general application. **Do not empty into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings.**

Maintenance:

For floors finished with LTP Ironwax Gloss or LTP Ironwax Satin use LTP Floorshine to clean and protect the floor. In areas where the seal becomes worn, apply a little more LTP Ironwax Gloss or LTP Ironwax Satin. At some stage, complete renovation of the seal may be desired. In this case use LTP Grimex to strip the surface seal before re-sealing.

This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area

LTP, Tone Estate, Milverton Road, Wellington, Somerset, TA21 0AN

Tel: 01823-666-213

Fax: 01823-665-685

www.ltp-online.co.uk

info@ltp-online.co.uk