



CLEANING - SEALING - MAINTENANCE

Sealing and maintenance solutions for all types of stone, porcelain, quarry, terracotta and glazed ceramic

TECH DATA SHEET 2010

FRONT:

LTP MPG Sealer

Polished Wall & Floor Tile Sealer

Impregnating sealer for polished porcelain, marble, limestone, slate & granite.
Suitable for interior & exterior use

BACK:

LTP MPG Sealer

Colourless and easy to apply impregnating sealer. Suitable for polished floors, walls, worktops and fireplaces. Does not alter the polished finish of the surface.

Directions for use:

Ensure surface is clean, dry and free from contamination. If necessary, first clean surfaces with LTP Grimex and allow to fully dry. NB: It is important to remove any factory applied sealer or wax from the surface of porcelain before sealing.

Apply thinly and uniformly using a soft cloth or sponge. Within 20 minutes, whilst the sealer is still wet on the surface, buff well using a clean dry cloth or buffing machine. Leave to dry for 4 hours and then on more porous surfaces apply a second coat using the same method. It is important to remember to remove any excess from the surface and buff well between each coat. Do not apply in temperatures exceeding 25°C. Ensure underfloor heating is switched off. Over applied and un-buffed sealer will dry and leave a greasy residue on the surface. To remove, apply white spirit or a little more sealer and then buff immediately. If you are unsure of correct application methods, test on an inconspicuous area, prior to general application. Treated areas should be dry enough to walk on after about 4 hours but will take 3 days to become fully water resistant.

Coverage:

Approximately 10 - 30 square metres/litre depending on surface porosity.

Maintenance:

Use LTP Waxwash for floors and LTP Stonewash for walls. For stubborn surface marks use LTP Grimex, in which case you may need to re-seal treated areas. Do not use strong bleach cleaners for routine maintenance.

HEALTH & SAFETY:

Contains: Naphtha (petroleum), hydrodesulfurized heavy: low boiling point (white spirit). FLAMMABLE. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.

Keep away from food, drink and animal feeding stuffs. Keep out of reach of children. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Wear suitable gloves. If swallowed, seek medical advice immediately and show this container or label. Use only in well ventilated areas. Avoid release to the environment. Refer to special instructions/Safety Data Sheets.

UN 1300

VOC STATEMENT

EU Limit value for this product (Cat A/h)
750g/L (2010)
This product contains max 739g/L VOC



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area

for beautiful surfaces we have the solutions...

LTP, Tone Estate, Milverton Road, Wellington, Somerset, TA21 0AN

T +44 (0) 1823 666213 F +44 (0) 1823 665685 E info@ltp-online.co.uk

www.ltp-online.co.uk

