

May 2009



## TECHNICAL DATA SHEET

FRONT:

### **LTP MATTSTONE**

### **NATURAL FINISH FLOOR SEALER**

FOR TRAVERTINE, STONE, SANDSTONE, SLATE, MARBLE, TERRACOTTA, QUARRY, BRICK & PAVING.

**SUITABLE FOR INTERIOR & EXTERIOR USE**

BACK:

#### **LTP Mattstone**

***Suitable for interior & exterior use.***

*A natural, matt finish impregnating sealer. Delicately enhances colour and texture. Helps protect against staining. Strongly repels water, oil and grease. Allows surface to breathe.*

#### ***Directions for use:***

Shake the bottle prior to use. Ensure surface to be treated is completely clean, dry and free from dirt, grime, cement and grout. Apply this sealer with a soft cloth or brush allowing at least two hours between coats. More absorbent floors may require further coats and on such floors the product should be generously applied. One hour after application, rub over the surface with a soft fluff free cloth or buffing machine to obtain a uniform finish and remove any material not yet absorbed. This product will dry after about two hours, but will take a further three days to become fully resistant. **N.B.** The aim is to completely fill the substrate with sealer without over applying it. Do not apply in direct sunlight. The sealer will help to inhibit oil based stains but such spillages should be wiped up immediately. On rougher surfaced floors it may be prudent to use an appropriate surface sealer in conjunction with this sealer.

#### ***Coverage:***

Lower porosity floors - approximately 1-2 litres per 10m<sup>2</sup> of floor

Higher porosity floors - approximately 3-4 litres per 10m<sup>2</sup> of floor

#### ***Maintenance:***

Routinely sweep the floor and wash with LTP Waxwash. Clean walls and work surfaces with LTP Stonewash Spray. For further information refer to the technical data sheet.

### **HEALTH & SAFETY**

#### **FLAMMABLE**

**Contains: naphtha(petroleum) hydrodesulphurised heavy (<0.1% benzene). Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.**

**Harmful: may cause lung damage if swallowed.**

**Repeated exposure may cause skin dryness or cracking.**

Keep away from food, drink and animal feeding stuffs. Keep out of the reach of children. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Wear suitable gloves. If swallowed, seek medical advice immediately and show this container or label. Use only in well ventilated areas. Avoid release to the environment. Refer to special instructions/Safety Data Sheets.

**UN 1300**



Very High VOC content, > 50%.  
VOC's (Volatile Organic Compounds) Contribute to atmospheric pollution.

This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area

**LTP, Tone Estate, Milverton Road, Wellington, Somerset, TA21 0AN**

**Tel: 01823-666-213 Fax: 01823-665-685**

**[www.ltp-online.co.uk](http://www.ltp-online.co.uk) [info@ltp-online.co.uk](mailto:info@ltp-online.co.uk)**