



# CLEANING ■ SEALING ■ MAINTENANCE

Sealing and maintenance solutions for all types of stone, porcelain, quarry, terracotta and glazed ceramic

## SOLVEX TECHNICAL DATA SHEET REF: 24/5/1

### LTP SOLVEX

High Performance Remover suitable for Wax, Silicone, Acrylic, Polyurethane Sealers and Residual Epoxy Grout For Stone, Travertine, Terracotta, Slate, Sandstone, Flagstones, Quarry Tiles, Glazed Ceramic and Porcelain. A powerful non-caustic stripper that softens most types of surface sealer, which can then be removed with ease. Suitable for removing most wax, oil, silicone, acrylic, polyurethane sealers and residual epoxy grout. After washing and rinsing, surfaces are ideal for re-sealing.

#### Directions for use:

Open the container and pour into a glass or metal container (not plastic). Apply generously by dapping on with a cloth or brush. Work in manageable areas of no more than 5 sq metre and do not brush out. Leave for approximately 30 minutes to ensure good penetration, but do not allow the solution to dry out. If drying should occur within 30 minutes apply a little more solution. Use a coarse, stiff brush or abrasive pad to remove softened coating from the surface. Repeat the process if unwanted material remains. Wash down with a dilute solution of LTP Grimex, rinse with plenty of water and leave to dry (min 24hrs) before re-sealing. Use Natural Fibre brushes to remove residues. Brushes made from synthetic fibres may be damaged by this product. If you are unsure of correct application methods, test on an inconspicuous area, prior to general application. If removing residues from epoxy grout; apply making sure to avoid prolonged contact with the joint as well. Viscous solution should not drip if used on vertical surfaces. Protect acrylic surfaces such as baths and shower trays from contact.

#### Health & Safety:

##### HEALTH & SAFETY

**CONTAINS: Benzyl Alcohol**

**Harmful if swallowed**

**Harmful if inhaled.**

Keep out of reach of children. Wash contaminated skin thoroughly after handling. Use only in well ventilated area. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Get medical advice/attention. Keep away from food, drink and animal feedingstuffs. Dispose of contents/container in accordance with local regulations. Do not eat, drink or smoke when using this product. Avoid breathing vapour/spray

WARNING



Label in accordance with (EC) No. 1272/2008

#### Coverage:

Light Stripping 8-10m<sup>2</sup>/litre

Deep Stripping 5m<sup>2</sup>/litre

#### Storage information:

Store in a cool, dry, frost free environment



*This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.*

*for beautiful surfaces we have the solutions...*

LTP, Tone Estate, Milverton Road, Wellington, Somerset, TA21 0AN

T +44 (0) 1823 666213 F +44 (0) 1823 665685 E info@ltp-online.co.uk

**www.ltp-online.co.uk**

July 11

