



TECHNICAL DATA SHEET

FRONT:

LTP STONE OIL

OIL BASED PRE-POLISH SEALER

FOR POROUS STONE & TERRACOTTA.

SUITABLE FOR INTERIOR & EXTERIOR USE

BACK:

LTP Stone Oil

Suitable for Interior & Exterior use.

Easy to apply oil based impregnating sealer ideal for low porosity porous stone and terracotta. Enhances the colour and texture of floors. Offers good mechanical strength once cured.

Directions for use: Shake well

Ensure surface to be treated is completely dry and free from contaminants which may prevent LTP Stone Oil from properly curing. Apply by brush or clean fluff-free cloth depending on the required application. Please note more porous floors may require more than one application, remove any excess sealer that has not been fully absorbed within 1 hour.

IMPORTANT:NB If using this product outside finish with a coat of LTP Mattstone to offer extra protection. Leave to cure for a minimum of 24 hours before finishing the surface with LTP Beeswax, LTP Ironwax Satin or LTP Ironwax Gloss.

Used cloths should be burnt after use as they may spontaneously combust.

Maintenance: For floors finished with LTP Ironwax Satin or Gloss. Routinely sweep the floor. Use LTP Floorshine to clean and protect the floor. In areas where the seal becomes worn, apply more sealer. On floors finished with LTP Beeswax use LTP Waxwash. At some stage, complete renovation of the seal may be desired. In this case use LTP Grimex to strip the surface before re-sealing.

Coverage: 1-2 litres per 10m² of floor

NB. Allow good ventilation during application. LTP Stone Oil may cure more rapidly in dry or higher temperature conditions. Avoid working in direct sunlight; rapid oxidation may inhibit effectiveness of the product. Not suitable for older floors that have no damp proof course.

HEALTH & SAFETY

Contains: White Spirit (naphtha petroleum, hydrodesulphurised heavy (<0.1% benzene) . FLAMMABLE. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful : may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.

Keep away from food, drink and animal feeding stuffs.

Keep out of the reach of children. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Wear suitable gloves. If swallowed, seek medical advice immediately and show this container or label. Use only in well ventilated areas. Avoid release to the environment. Refer to special instructions/Safety Data Sheets.

UN 1300



Very High VOC content, > 50%.
VOC's (Volatile Organic Compounds) Contribute to atmospheric pollution.

This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area

LTP Tone Estate, Milverton Road, Wellington, Somerset, TA21 0AN

Tel: 01823-666-213

Fax: 01823-665-685

www.ltp-online.co.uk

info@ltp-online.co.uk