



CLEANING ■ SEALING ■ MAINTENANCE

Sealing and maintenance solutions for all types of stone, porcelain, quarry, terracotta and glazed ceramic

STONE OIL ANTIQUE TECHNICAL DATA SHEET REF: 27/5/1

LTP STONE OIL ANTIQUE

Pre-Polish Ageing Oil

For natural stone & terracotta

Interior & exterior use

A unique pre-polish oil for making new stone and terracotta look instantly "aged"

Directions for use:

Ensure surface to be treated is completely dry and free from contaminants which may prevent LTP Stone Oil Antique from properly curing. Apply by brush or soft cloth and allow to cure thoroughly (minimum 12 hours) before polishing with LTP Antique Beeswax. The action of applying the beeswax removes some of the LTP Stone Oil Antique and it is the remaining LTP Stone Oil Antique beneath the polish which provides the "aged" appearance. The longer the oil is allowed to cure, the more difficult it is to remove and the darker the finish will be. For an even darker finish a second coat may be applied and allowed to cure thoroughly. This should be done before use of the beeswax.

Health & Safety:

HEALTH & SAFETY

Contains: White Spirit (naphtha petroleum,hydrodesulphurised heavy (<0.1% benzene) . FLAMMABLE. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful : may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.

Keep away from food,drink and animal feeding stuffs. Keep out of reach of children. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Wear suitable gloves. If swallowed, seek medical advice immediately and show this container or label. Use only in well ventilated area. Avoid release to the environment. Refer to special instructions/Safety Data Sheets.



VOC STATEMENT
EU Limit value for this product
(Cat A/h) 750g/L (2010)
This product contains max
597g/L VOC

UN 1300

Coverage:

Approximately 10 sq m per litre (one coat)

Storage Information:

Store in a cool, dry, frost free environment

Maintenance:

Avoid using strong detergents and kitchen cleaners to wash surfaces finished with LTP Beeswax. Use LTP Waxwash to wash the floor and buff when dry. Re-polish any dull areas with LTP Beeswax.

Notes:

IMPORTANT:NB If using this product outside finish with a coat of LTP Mattstone to offer extra protection. Experiment before general application, so that methods of use are fully understood. On more absorbent stone or terracotta it may be necessary to use a suitable impregnating sealer before application of LTP Stone Oil Antique, e.g LTP Boiled Linseed Oil or Mattstone.Shake bottle before use. Used cloths should be burnt after use as they may spontaneously combust. Allow good ventilation during application. LTP Stone Oil may cure more rapidly in dry or higher temperature conditions. Avoid working in direct sunlight; rapid oxidation may inhibit effectiveness of the product. Not suitable for older floors that have no damp proof course.



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area

for beautiful surfaces we have the solutions...

LTP, Tone Estate, Milverton Road, Wellington, Somerset, TA21 0AN

T +44 (0) 1823 666213 F +44 (0) 1823 665685 E info@ltp-online.co.uk

www.ltp-online.co.uk

July 2011

